

PRODUCT INFORMATION

EPIC® DATA CAN TR M12

M12 Terminating resistor for DeviceNet/CANopen

Extremely robust M12 bus termination (resistor) for individuell use within field bus networks (PROFIBUS, DeviceNet and CANopen).

Info

Fully suitable for industrial use





DeviceMet CRNopen



Supplementary automation components from Lapp



Assembly time



Space requirement

Benefits

Cost efficient termination of a bus systems Space-saving due to compact dimensions. Robust design

Application range

Mechanical and plant engineering

Product features 120 Ω terminating resistor for DeviceNet/CANopen

Product Make-up Straight connector M12 with integrated termination resistor

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000448

Last Update (23.04.2024) ©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02_03.16



EPIC® DATA CAN TR M12

	ETIM 5.0 Class-Description: Terminal resistor	
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000448 ETIM 6.0 Class-Description: Terminal resistor	
Protection rating:	IP65/IP67	
Ambient temperature (operation):	-25°C to +90°C	
Contact material:	CuSn	
Coding:	A - Standard (CANopen/DeviceNet)	
Rated current (A):	4 A	

Note

DeviceNet is a registered trademark of ODVA

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update ©2024 Lap	Article number	Article designation	Number of pins	Rated voltage (V)	PU	
	Plug, unshielded (terminating resistor)					
	22260766	AB-C5-M12MS-DN-TR	5	60	5	
Last Update (23.04.2024) ©2024 Lapp Group - Technical changes reserved						

EPIC® DATA CAN TR M12

©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02_03.16