

Innovative metal and plastic housing design

The robust compact plastic housing has a side cable entry and is suitable for use in machine and device manufacturing.

Info

Lightweight, chemically resistant plastic housing Protection rating UL50E tested











Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

Benefits

Housing in plastic or metal version for safe connections in the smallest possible space

Application range

Machine and equipment manufacturing Control engineering Electronic laboratory

Product features

Hood
Bolts for single lever
Side cable entry
Versions with / without cable gland

Last Update (28.04.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16





Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: thermoplastic, grey, black

Lever: zinc-plated steel

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

PG Cable gland Pieces / PU Article number Article description Material Colour Cable clamping range 11 10 10427300 H-A 3 Ts Thermoplastic black 10427000 11 Thermoplastic 10 H-A 3 Ts grey 10620600 H-A3Ts 11 6.5 - 12 10 Thermoplastic black yes 11 10427100 H-A 3 Ts Thermoplastic 6.5 - 12 10 grey yes 19427300 H-A 3 MTSV 7-13 20 10 Thermoplastic black H-A 3 MTSV 7-13 19427000 20 10 Thermoplastic grey



