

## ETB Label holders

ETB Marking labels are cable ties with labelling area for bundling and marking cables and conduits



Halogen-free



UV-resistant

### Benefits

Suitable for binding and bundling

The label holder can be opened and closed easily to replace the label

Good UV-resistance

### Application range

Marking cables, tubes, items, or as advertising media, baggage labels and any other kind of labelling

### Product features

The label is folded in a way that can be reduced to a quarter of its size, matching the visible part of the printing field in the label holder

### Included

61742810: including marking labels (2 sheets with 56 labels each)

### Product Make-up

Cable tie dimensions: 200 x 5 mm

Perforated cardboard (colour: white)

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001288

ETIM 5.0 Class-Description: Labelling material

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001288

ETIM 6.0 Class-Description: Labelling material

Material:

Polypropylene (PP)

Temperature range:

-18 °C bis +90 °C

Mounting temperature: min. +10 °C

Last Update (23.02.2025)

©2025 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ETB Label holders

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

FLEXIMARK® products are sold in packaging units. As example if you like to order 640 labels of LCK 32 you just need to order 1 PU instead of 640 single labels.

## ETB Label holders

Article number	Article designation	Width x height (mm)	Labels per side	Contents (unit)
61742810	ETB holder transparent	60 x 33	-	50
61742900	ETB labels	52 x 17.5	56	1

Last Update (23.02.2025)

©2025 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16