

## ETHERLINE® ACCESS U

Industrial unmanaged Ethernet switches

Industrial network switches for ethernet based solutions in Smart Factories.

### Info

Redundant power inputs

Robust metal housing and DIN rail mounting



Supplementary automation components from Lapp



Mechanical and plant engineering

### Benefits

Improve your total cost of ownership with faster installation and lower downtime

Most flexible and globally present solutions from one hand

### Product features

RJ45 Ports: 10/100/1000 BaseT(X)

Packet Buffer Size: min. 1Mbit

Broadcast storm protection

Redundant Power Input: 24 VDC

### Norm references / Approvals

UL 61010

Shock IEC 60068-2-27

Freefall IEC60068-2-32

Vibration IEC 60068-2-6

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000734

Last Update (14.05.2026)

©2026 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**ETHERLINE® ACCESS U**

Classification ETIM 6:	ETIM 5.0 Class-Description: Network switch ETIM 6.0 Class-ID: EC000734 ETIM 6.0 Class-Description: Network switch
power supply:	DC 24 V (18-30 V DC)
Protection rating:	IP 30
Temperature range:	-10°C to +60°C

**Note**

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**ETHERLINE® ACCESS U**

Article number	Article designation	Type	number of ports
Unmanged switches with RJ45			
21700123	ETHERLINE® ACCESS U05T-2GEN	Unmanaged	5 x RJ45
21700124	ETHERLINE® ACCESS U08T-2GEN	Unmanaged	8 x RJ45
21700120	ETHERLINE® ACCESS U16T	Unmanaged	16 x RJ45
Gigabit Unmanaged switches			
21700129	ETHERLINE® ACCESS U08GT	Unmanaged	8 x RJ45
21700153	ETHERLINE ACCESS U04GTP01GT	Unmanaged	5 x RJ45

Last Update (14.05.2026)

©2026 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03\_16