

UNITRONIC® BUS CAN M12

DeviceNet/CANopen Cable: M12 plug/socket on free conductor end

Robust, pre-assembled DeviceNet M12 (A-coded) cable with PUR (halogen-free) outer sheath for flexible use (drag chain). Shielded version.

Info

Other types are available at www.lappgroup.com/assemblyfinder or on request





DeviceMed CRINICOSO

Supplementary automation components from Lapp



Mechanical and plant engineering



Assembly time



Power chain

Benefits

Cost-effective, efficient wiring of fieldbus and sensor/ actuator installations Space-saving due to compact dimensions.
Fast and easy error tracking
Robust design

Application range

Mechanical and plant engineering

Product features

5-core DeviceNet/CANopen cable, shielded M12 connector, A-coded with quick-locking system

Last Update (09.10.2025)
©2025 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



UNITRONIC® BUS CAN M12

Suitable for drag chains Including tag carrier

Norm references / Approvals

UL-AWM-Style 21198 (80 °C / 300 V)

Product Make-up

Signal line: 2 x 0.25 mm² Power supply: 2 x 0.34 mm² Drain wire: 1 x 0.34 mm²

Core colours: red/black, blue/white Outer sheath: PUR halogen-free, violett

Outer diameter: 6.7 mm Shielded version

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC001855

ETIM 5.0 Class-Description: Sensor-actuator patch cord

Classification ETIM 6: ETIM 6.0 Class-ID: EC001855

ETIM 6.0 Class-Description: Sensor-actuator patch cord

Material: Contact: CuSn

Contact surface: Ni/Au

Knurl: Zinc die-cast, nickel-plated

Gripping body: TPU, flame-retardant, self-extinguishing

Protection rating: IP65/IP67

Ambient temperature (operation): Plug/socket -25°C to +90°C

Fixed installation -40°C to +80°C

Flexing -20°C to +70°C

Coding: A-standard

Rated current (A): 4 A

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: inclusive of copper. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



UNITRONIC® BUS CAN M12

Article number	Article designation	Length (m)	Number of pins	Design	Rated voltage (V)	PU
Plug						
22260789	AB-DN-M12MS-2,0PUR	2	5	straight	60	1
22260790	AB-DN-M12MS-5,0PUR	5	5	straight	60	1
22260791	AB-DN- M12MS-10,0PUR	10	5	straight	60	1
22262004	AB-DN-M12MA-2,0PUR	2	5	angled	60	1
Socket						
22260792	AB-DN-2.0PUR-M12FS	2	5	straight	60	1
22260793	AB-DN-5.0PUR-M12FS	5	5	straight	60	1
22260794	AB-DN-10.0PUR-M12FS	10	5	straight	60	1