

Connector system for weatherproof cabling of photovoltaic systems

Info

4 mm connector system with double hook Splitter for parallel connection of photovoltaic modules





Solar Energy



Suitable for outdoor use



Voltage



Temperature-resistant



UV-resistant



Waterproof

Benefits

Splitter for pallalel connection of PV-modules and strings Easy plug and play Fixing option for a clear installation with a \varnothing 5mm mounting hole

Application range

Photovoltaic plants Crystalline and thin-film constructions Solartracker

Product features

Mateable with EPIC® SOLAR 4 THIN, EPIC® SOLAR 4PLUS, EPIC® SOLAR 4

Last Update (06.01.2025)
©2025 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



Splitter MFF 1x connection male, 2x connection female Splitter MFF 1x connection female, 2x connection male

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC002635

ETIM 5.0 Class-Description: Circular connector (industrial

connector)

Classification ETIM 6: ETIM 6.0 Class-ID: EC002635

ETIM 6.0 Class-Description: Circular connector (industrial

connector)

Rated voltage (V): 1000 V AC/DC

Rated impulse voltage: 8 kV
Rated current (A): 30 A
Pollution degree: 3

Protection rating: IP65/IP67

Cycle of mechanical operation: 100
Protection class: II

Temperature range: -40 °C ... +85 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



Article number Article designation PU EPIC® SOLAR 4 Splitter 44428226 EPIC® SOLAR 4 Splitter MFF 25 44428227 EPIC® SOLAR 4 Splitter FMM 25



