

SKINDICHT® ZSE-M

SKINDICHT® ZSE-M, hexagonal converter from a metric outer thread to a PG inner thread, assembling with a wrench



Robust

Benefits

Enables the use of PG accessories in metric threads
Assembling with a wrench

Application range

Hexagonal converter from a metric outer thread to a PG inner thread.
Machines
Devices
Housings

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Note

SKINDICHT® ZSE-M-XL offers a long metric connection thread

Product Make-up

These converters are used in our cable glands:
SKINDICHT® SHV-M
SKINDICHT® SHVE-M
SKINDICHT® SRE-M
SKINDICHT® SR-SV-M

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Material:

Body: nickel-plated brass

Last Update (10.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINDICHT® ZSE-M

Temperature range: -60 °C to +200 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SKINDICHT® ZSE-M

Article number	Thread, male M1	Thread, female PG	Pieces / PU
SKINDICHT® ZSE-M			
52106000	12 x 1.5	7	100
52106010	16 x 1.5	9	100
52106020	20 x 1.5	11	100
52106030	20 x 1.5	13.5	100
52106040	20 x 1.5	16	50
52104050	20 x 1.5	21	50
52106050	25 x 1.5	21	50
52106060	32 x 1.5	29	25
52106070	40 x 1.5	36	10
52106080	50 x 1.5	42	10
52106090	63 x 1.5	48	10
SKINDICHT® ZSE-M-XL			
52106005	12 x 1.5	7	100
52106015	16 x 1.5	9	100
52106025	20 x 1.5	11	100
52106035	20 x 1.5	13.5	100
52106045	20 x 1.5	16	50
52106055	25 x 1.5	21	50
52106065	32 x 1.5	29	25

Last Update (10.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16