

## SKINDICHT® TWIST-M

Swivelling coupler with hexagonal collar

SKINDICHT® TWIST-M, swivelling coupler with metric connection thread for exact positioning of elbowed fittings



Good chemical resistance



Halogen-free



Corrosion-resistant



Temperature-resistant



Torsion-resistant



UV-resistant

### Benefits

Exact positioning of e.g. elbowed fittings

Swivelling coupler with increased sealing

Prevents cables and conduits to get damaged due to (unintentionally) encountered torsional stress

### Application range

Control cabinet manufacturing

Control systems

Mechanical engineering

For mobile equipment and machines

In combination with metric threaded (conduit) fittings

### Product features

Swivelling upper part

High sealing performance

Last Update (02.05.2024)

©2024 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## SKINDICHT® TWIST-M

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable screw gland
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000441 ETIM 6.0 Class-Description: Cable screw gland
Note:	On request: size M12, M32, M40, M50, M63
Material:	Body: nickel-plated brass Spring ring: spring steel Sealing: FKM
Protection rating:	IP 68
Temperature range:	-20°C up to +200°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINDICHT® TWIST-M**

Article number	Thread, male M1	Thread, female M2	SW wrench size mm	Pieces / PU
52104731	16 x 1.5	16 x 1.5	20	10
52104732	20 x 1.5	20 x 1.5	24	10
52104733	25 x 1.5	25 x 1.5	29	5

Last Update (02.05.2024)

©2024 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16