

SKINTOP® DIX-AUTOMATION

SKINTOP® DIX-AUTOMATION, NBR seals with optimal seal when using AS-I bus cables, strain relief



UV-resistant



Temperature-resistant



Reliability



Assembly time



Kompletterande automationskomponenter från Lapp

Benefits

Optimal seal when using AS-I bus cables

Strain relief

Application range

These seals can be used instead of our standard seals in the SKINTOP® cable glands.

Control cabinets

Control panels

Office applications

Note

IP 68 can be achieved if the hole is optimally occupied, i.e. when using standard AS-I cables

Product Make-up

Precise cut for AS-I bus cables

Last Update (25.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINTOP® DIX-AUTOMATION

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000032 ETIM 5.0 Class-Description: Plug for cable screw gland
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000032 ETIM 6.0 Class-Description: Plug for cable screw gland
Colour delivered:	Black, RAL 9005
Material:	NBR
Protection rating:	IP 54
Temperature range:	-40°C to +100°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



SKINTOP® DIX-AUTOMATION

Article number	Article designation / size
SKINTOP® DIX ASI	
53611000	DIX ASI 11

Last Update (25.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16