

EPIC® DATA CAN TR M12

M12 Terminating resistor for DeviceNet/CANopen

Extremely robust M12 bus termination (resistor) for individual use within field bus networks (PROFIBUS, DeviceNet and CANopen).

Info

Fully suitable for industrial use



Supplementary automation components from Lapp



Assembly time



Space requirement

Benefits

Cost efficient termination of a bus systems
Space-saving due to compact dimensions.
Robust design

Application range

Mechanical and plant engineering

Product features

120 Ω terminating resistor for DeviceNet/CANopen

Product Make-up

Straight connector M12 with integrated termination resistor

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000448

Last Update (19.12.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® DATA CAN TR M12

Classification ETIM 6:	ETIM 5.0 Class-Description: Terminal resistor ETIM 6.0 Class-ID: EC000448 ETIM 6.0 Class-Description: Terminal resistor
Protection rating:	IP65/IP67
Ambient temperature (operation):	-25 °C to +90 °C
Contact material:	CuSn
Coding:	A - Standard (CANopen/DeviceNet)
Rated current (A):	4 A

Note

DeviceNet is a registered trademark of ODVA

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® DATA CAN TR M12

Article number	Article designation	Number of pins	Rated voltage (V)	PU
Plug, unshielded (terminating resistor)				
22260766	AB-C5-M12MS-DN-TR	5	60	5

Last Update (19.12.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16