

# EPIC® H-A 16 AD-LB

These connectors are attractive because of their compact housing.

The compact housing for rectangular connectors is ideal for use in machine and device manufacturing and is supplied with a seal.

## Info
Metal lid with sturdy hinge
Protection rating UL50E tested






Waterproof

Robust

Mechanical resistance

Mechanical and plant engineering

## Benefits
Small and compact, for applications with high number of contacts

## Application range
Machine and equipment manufacturing
Control engineering
Electronic laboratory

## Product features
H-A case: Wall base
Single lever
Metal cover
Included: flat gasket

Last Update (22.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

# EPIC® H-A 16 AD-LB

## Technical Data

| | |
|---|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000437<br>ETIM 5.0 Class-Description: Housing for industrial connectors |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000437<br>ETIM 6.0 Class-Description: Housing for industrial connectors |
| Material: | Housing: aluminium alloy, grey<br>Lever: zinc-plated steel<br>Sealing: NBR |
| Protection rating: | IP 65 (latched)<br>NEMA 250, UL50E: 12, 4 (latched) |
| VDE-tested: | Certified production control: VDE-REG. no.: B437<br>UL-tested:<br>UL File Number: E75770 |
| Temperature range: | -40 °C to +100 °C, short-term up to +125 °C |

## Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.


©2024 Lapp Group - Technical changes reserved

# EPIC® H-A 16 AD-LB

| Article number | Article description | M |
|---|---|---|
| H-A housing: panel-mount base (cover, single lever) | | |
| 70474000 | H-A 16 AD-LB | AG |

Last Update (22.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16