

## EPIC® H-A 3 AG

Innovative metal and plastic housing design

The compact plastic or metal housing for rectangular connectors is ideal for use in restricted spaces.

### Info

Lightweight, chemically resistant plastic housing

Protection rating UL50E tested



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

### Benefits

Housing in plastic or metal version for safe connections in the smallest possible space

### Application range

Machine and equipment manufacturing

Control engineering

Electronic laboratory

### Product features

H-A case: Wall base

1 lever

Anbauehäuse mit Deckel (mit Dichtung, für Buchseneinsätze)

Panel-mount base, flat gasket included (version with open base)

Last Update (05.06.2023)

©2023 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## EPIC® H-A 3 AG

Included: flat gasket

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000437 ETIM 5.0 Class-Description: Housing for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000437 ETIM 6.0 Class-Description: Housing for industrial connectors
Material:	Housing: powder-coated zinc die-casting, grey Lever: zinc-plated steel Sealing: NBR Housing: grey thermoplastic, black Lever: zinc-plated steel Sealing: NBR
Protection rating:	IP 65 (latched) NEMA 250, UL50E: 12, 4 (latched)
VDE-tested:	Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770
Temperature range:	-40°C to +100°C, short-term up to +125°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

**EPIC® H-A 3 AG**

Article number	Article description	M	Material	Colour	Pieces / PU
H-A housing: panel-mount base (straight)					
10422500	H-A 3 Mag	AG	Zinc die-casting	grey	10
10422200	H-A 3 Ag	AG	Thermoplastic	black	10
10422000	H-A 3 Ag	AG	Thermoplastic	grey	10

Last Update (05.06.2023)

©2023 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03\_16

**EPIC® H-A 3 AG**