

EPIC® H-B 10 SDRH-BO


Housing design H-B. The industry standard.

The universal metal housing with pivots for a direct lever and a cable entry is suitable for use in the plastics industry and investment construction.

Info

More interior space for wiring Metal lid with sturdy hinge Protection rating UL50E tested









Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

Benefits

The smallest housing with single and double lever. The right housing is available for every application

Application range

Plant engineering Light & sound technology Plastics industry

Last Update (14.07.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



EPIC® H-B 10 SDRH-BO

Product features

Surface-mount base, high version Bolts for double lever 1 cable entry Metal cover

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

IP 40 (cover closed)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® H-B 10 SDRH-BO

Article numberArticle descriptionMPGPackaging unitH-B housing: surface-mount base (cver, 1 cable entry, bolts for double lever, high version)70045200H-B 10 SDRH-BO 21-21579045200H-B 10 SDRH-BO M2525-5