

EPIC® H-B 10 TGB

Housing design H-B. The industry standard.

The universal metal housing is suitable for lighting and sound systems. It has 2 double levers and a direct cable entry.

Info

- Non-slip ridges for comfortable disconnecting
- For connection with counterpart with integrated cover
- Protection rating UL50E tested



- Supplementary automation components from Lapp
- Mechanical and plant engineering
- Mechanical resistance
- Robust
- Waterproof

Benefits

The smallest housing with single and double lever. The right housing is available for every application
 Double lever version with 2 levers for increased safety

Application range

- Plant engineering
- Light & sound technology
- Plastics industry

Last Update (15.07.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® H-B 10 TGB

Product features

Hood, low version
Dual levers
Straight cable entry
Versions with / without neck

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000437 ETIM 5.0 Class-Description: Housing for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000437 ETIM 6.0 Class-Description: Housing for industrial connectors
Material:	Housing: powder-coated aluminium alloy, grey Lever: zinc-plated steel Sealing: NBR
Protection rating:	IP 65 (latched) NEMA 250, UL50E: 12, 4 (latched)
VDE-tested:	Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770
Temperature range:	-40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® H-B 10 TGB

Article number	Article description	M	PG	Neck	Packaging unit
H-B housing: hood (straight cable entry, double lever)					
10041000	H-B 10 TGB 16	-	16	yes	10
19041000	H-B 10 TGB M20	20	-	-	10
79055700	H-B 10 TGB M25	25	-	-	10

Last Update (15.07.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16