

# **EPIC® H-B 10 TSH-RO**

Housing design H-B. The industry standard.

The universal high metal housing has pivots for a single lever and a side cable entry. It is suitable for use in the plastics industry.

## Info

Non-slip ridges for comfortable disconnecting More interior space for wiring Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

## Benefits

The smallest housing with single and double lever. The right housing is available for every application

# **Application range**

Plant engineering Light & sound technology Plastics industry

# **Product features**

Last Update (24.04.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16



# **EPIC® H-B 10 TSH-RO**

Hood, high version Reels for single lever Side cable entry Versions with / without neck

**Technical Data** 

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

# Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



# **EPIC® H-B 10 TSH-RO**

Article number	Article description	М	PG	Neck	Pieces / PU
H-B housing: hood (side cable entry, bolts for single lever, high version)					
70054200	H-B 10 TSH-RO 21	-	21	yes	10
70054400	H-B 10 TSH-RO 29	-	29	yes	10
79054200	H-B 10 TSH-RO M25	25	-	-	10
79054400	H-B 10 TSH-RO M32	32	-	-	10