EPIC® H-B 16 SGRH-LB

Housing design H-B. The industry standard.

The robust low base housing is ideal for use in the plastics industry and consists of 2 cable entries and a single lever.

Info
Single Lever version for quick locking and simple unlocking with lifting aid
More interior space for wiring
Protection rating UL50E tested

Supplementary automation components from Lapp

Mechanical and plant engineering

Mechanical resistance

Robust

Waterproof

Benefits
The housing standard. Wide choice for all applications

Application range
Plant engineering
Light & sound technology
Plastics industry

Product features

EPIC® H-B 16 SGRH-LB

Surface-mount base, high version
Single lever
1 cable entry

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000437
	ETIM 5.0 Class-Description: Housing for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000437
	ETIM 6.0 Class-Description: Housing for industrial connectors
Material:	Housing: powder-coated aluminium alloy, grey
	Lever: zinc-plated steel
	Sealing: NBR
Protection rating:	IP 65 (latched)
	UL50 Type 12 (latched)
VDE-tested:	Certified production control: VDE-REG. no.: B437
	UL-tested:
	UL File Number: E75770
Temperature range:	-40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article description	M	PG	Pieces / PU
H-B housing: surface-mount base (1 cable entry, single lever, high version)				
70110200	H-B 16 SGRH-LB 21	-	21	5
70110400	H-B 16 SGRH-LB 29	-	29	5
79110200	H-B 16 SGRH-LB M25	25	-	5
79110400	H-B 16 SGRH-LB M32	32	-	5