

EPIC® H-B 16 TBFH

Housing design H-B. The industry standard.

The robust metal housing consists of 2 double levers and a direct cable entry and is not only the ideal solution for application within the plastics industry.

Info

More interior space for wiring Double lever version with 2 levers for increased safety Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

Benefits

The housing standard. Wide choice for all applications

Application range

Plant engineering Plastics industry Light & sound technology

Last Update (21.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



EPIC® H-B 16 TBFH

Product features

Cable coupler hood, high version Dual levers Straight cable entry Versions with / without neck

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® H-B 16

TBFH

М PG Pieces / PU Article number Article description Neck H-B housing: cable coupler hood (straight cable entry, double lever, high version) 5 70090200 H-B 16 TBFH 21 21 yes 29 5 H-B 16 TBFH 29 70090400 yes 5 79090200 H-B 16 TBFH M25 25 32 5 79090400 H-B 16 TBFH M32 5 H-B 16 TBFH 2xM32 79090401 2 x 32