EPIC® H-B 24 TG-RO


Housing design H-B. The industry standard.


The robust metal housing with pivots for a single lever and a direct cable entry is not only ideal for use within the plastics industry.

Info
Non-slip ridges for comfortable disconnecting
Protection rating UL50E tested









Supplementary automation components from Lapp

Mechanical and plant engineering

Mechanical resistance

Robust

Waterproof

Benefits
Ideal for many applications due to a wide range of housings and inserts

Application range
Plant engineering
Light & sound technology
Plastics industry

Product features
Hood, low version

Last Update (22.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® H-B 24 TG-RO

Reels for single lever
Straight cable entry
Versions with / without neck

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000437 ETIM 5.0 Class-Description: Housing for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000437 ETIM 6.0 Class-Description: Housing for industrial connectors
Material:	Housing: powder-coated aluminium alloy, grey Lever: zinc-plated steel Sealing: NBR
Protection rating:	IP 65 (latched) NEMA 250, UL50E: 12 (latched)
VDE-tested:	Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770
Temperature range:	-40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2023 Lapp Group - Technical changes reserved

LAPP

EPIC® H-B 24 TG-RO

PRODUCT INFORMATION

Article number	Article description	M	PG	Neck	Pieces / PU
H-B housing: hood (straight cable entry, bolts for single lever)					
10121900	H-B 24 TG-RO 21	-	21	yes	5
10111900	H-B 24 TG-RO 29	-	29	yes	5
19121900	H-B 24 TG-RO M25	25	-	-	5
19111900	H-B 24 TG-RO M32	32	-	-	5

Last Update (22.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16