

EPIC® H-B 6 TBF-LB

Housing design H-B. The industry standard.

The universal metal housing with a direct cable entry is suitable for use in investment construction and the plastics industry.

Info

Protection rating UL50E tested







Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

Benefits

The smallest housing out of the H-B series. For inserts with high electrical properties

Application range

Plant engineering Control engineering Plastics industry

Product features

Cable coupler hood, low version Single lever Straight cable entry

Last Update (12.07.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



EPIC® H-B 6 TBF-LB

Versions with / without neck

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® H-B 6 TBF-LB

| Article number | Article description | М | PG | Neck | Packaging unit |
|------------------------------------------------------------------------|---------------------|----|------|------|----------------|
| H-B housing: cable coupler hood (1 straight cable entry, single lever) | | | | | |
| 10014000 | H-B 6 TBF 13,5 | - | 13.5 | yes | 10 |
| 10024000 | H-B 6 TBF 16 | - | 16 | yes | 10 |
| 19014000 | H-B 6 TBF M20 | 20 | - | - | 10 |
| 19024000 | H-B 6 TBF M25 | 25 | - | - | 10 |