
EPIC® H-BVE 10


These high-voltage inserts are additionally equipped with 2 switching contacts


The multi-pole insert enables switching operation for disconnecting loads and can be used in investment construction.

Info

Multipole insert with lagging switch contacts
Switching operations possible for disconnecting under load







Temperature-resistant

Benefits

With the relevant wiring, the lagging switch contacts interrupt the power supply before the working contacts are separated
These high-voltage inserts are additionally equipped with 2 switching contacts

Application range

Mechanical engineering
Plant engineering

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000438 ETIM 5.0 Class-Description: Contact insert for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000438 ETIM 6.0 Class-Description: Contact insert for industrial connectors
Rated voltage (V):	IEC: 630 V UL: 600 V CSA: 600 V
Rated impulse voltage:	6 kV
Rated current (A):	IEC: 16 A

Last Update (26.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® H-BVE 10

	UL: 16 A CSA: 16 A
Pollution degree:	3
Contact resistance:	< 2 mOhm
Contacts:	Copper alloy, hard silver-plated
Number of contacts:	10 + 2 + PE
Termination methods:	Screw termination: 0.5 - 2.5 mm²
Stripping length (mm):	8
Cycle of mechanical operation:	100
VDE-tested:	Certified production control: VDE-REG. no.: B437 UL-tested: UL File Number: E75770
Temperature range:	-40 °C to +100 °C, short-term up to +125 °C

Note
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2023 Lapp Group - Technical changes reserved

LAPP


EPIC® H-BVE 10

PRODUCT INFORMATION

Article number	Article description	Contact type	Wire protection	Number of operating contacts	Pieces / PU
H-BVE 10 screw termination					
10270010	H-BVE 10 SS	male	yes	10 + 2	5
10271010	H-BVE 10 BS	female	yes	10 + 2	5
10270110	H-BVE 10 SS	male	-	10 + 2	5
10271110	H-BVE 10 BS	female	-	10 + 2	5

Last Update (26.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® H-BVE 10



©2023 Lapp Group - Technical changes reserved