

EPIC® MC Module: 3pole

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

The three-pole signal module contains 3 contacts and is suitable for use in control systems, investment construction and printing presses.

Info

Very high current transfer in a small space







Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications

Application range

Plant engineering Printing machines Control engineering

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial connector)

Classification ETIM 6: ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial connector)

Last Update (12.07.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16





EPIC® MC Module: 3pole

Rated voltage (V): 630 V
Rated current (A): 40
Pollution degree: 3

Contact resistance: < 2 mOhm

Contacts: Copper alloy, hard silver-plated

Number of contacts: 3

Termination methods: Crimp termination: 1.5 - 10 mm²

Cycle of mechanical operation: 100

VDE-tested: UL-tested:

UL File Number: E75770

Temperature range: -40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® MC Module: 3pole

Contact type Number of operating contacts | Slots Packaging unit Article number Article description Module: 3-pin MCS 3 CM 10 10382000 male мсв з см 3 10 10382100 female