

EPIC® MC Module: Cage clamp 4pole

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

The module with spring-type terminal ensures fast connection with spring pin and has 4 contacts. It can be used, for example, in printing presses.

Info

Fast connection by cage spring







Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications

Application range

Plant engineering Printing machines Control engineering

Technical Data

Classification ETIM 6:

Classification ETIM 5: ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial connector)

connec

ETIM 6.0 Class-ID: EC002641 ETIM 6.0 Class-Description: Modular connector (industrial

connector)

Last Update (12.07.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



EPIC® MC Module: Cage clamp 4pole

Rated voltage (V): 400 V
Rated current (A): 14 A
Pollution degree: 3

Contact resistance: 1.5 - 4 mohm

Contacts: Copper alloy, hard silver-plated

Number of contacts: 4

Termination methods: Cage clamp termination: 0.5 - 2.5 mm²

Stripping length (mm): 10

Cycle of mechanical operation: 100

Temperature range: -40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® MC Module: Cage clamp 4pole

Contact type Number of operating contacts | Slots Packaging unit Article number Article description Module: 4-pin cage clamp MCS 4 F 10 10399600 male MCB 4 F 10 10399700 female