

EPIC® MC Module: Cage clamp 4pole

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

The module with spring-type terminal ensures fast connection with spring pin and has 4 contacts. It can be used, for example, in printing presses.

Info

Fast connection by cage spring



Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

The mix of different functions in one plug guarantees high flexibility
 Assembly of individual connectors, suitable for different applications

Application range

Plant engineering
 Printing machines
 Control engineering

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial connector)

Classification ETIM 6:

ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial connector)

Last Update (23.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® MC Module: Cage clamp 4pole

Rated voltage (V):	400 V
Rated current (A):	14 A
Pollution degree:	3
Contact resistance:	1.5 - 4 mohm
Contacts:	Copper alloy, hard silver-plated
Number of contacts:	4
Termination methods:	Cage clamp termination: 0.5 - 2.5 mm ²
Stripping length (mm):	10
Cycle of mechanical operation:	100
Temperature range:	-40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® MC Module: Cage clamp 4pole

Article number	Article description	Contact type	Number of operating contacts	Slots	Pieces / PU
Module: 4-pin cage clamp					
10399600	MCS 4 F	male	4	1	10
10399700	MCB 4 F	female	4	1	10

Last Update (23.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16