

## EPIC® MC Module: HE 4pole

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

The combination of a greater number of functions in this connector guarantees a high level of flexibility and it can therefore be used, for example, in printing presses.

### Info

Lever for rapid removal of the module



Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

### Benefits

The mix of different functions in one plug guarantees high flexibility  
 Assembly of individual connectors, suitable for different applications

### Application range

Plant engineering  
 Printing machines  
 Control engineering

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial connector)

Classification ETIM 6:

ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial connector)

Rated voltage (V):

630 V

Rated current (A):

25 A

Last Update (27.07.2024)

©2024 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## EPIC® MC Module: HE 4pole

|                                |  |
|--------------------------------|--|
| Pollution degree:              | 3  |
| Contact resistance:            | < 2 mOhm                                     |
| Contacts:                      | Copper alloy, hard silver-plated             |
| Number of contacts:            | 4  |
| Termination methods:           | Crimp termination: 0.5 - 4.0 mm <sup>2</sup> |
| Cycle of mechanical operation: | 100  |
| Temperature range:             | -40°C to +100°C, short-term up to +125°C     |

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**EPIC® MC Module: HE 4pole**

| Article number   | Article description | Contact type | Number of operating contacts | Slots | Packaging unit |
|------------------|---------------------|--------------|------------------------------|-------|----------------|
| Module: 4-pin HE |                     |              |                              |       |                |
| 10399000         | MCS 4 CM            | male         | 4                            | 1     | 10             |
| 10399100         | MCB 4 CM            | female       | 4                            | 1     | 10             |

Last Update (27.07.2024)

©2024 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03\_16