

EPIC® MC Module: PROFIBUS DP

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

PROFIBUS DP module is suitable for continuous bus operation and has screw termination, which ensures easy installation.

Info

Profibus DP module for uninterrupted fieldbus operation
Lever for rapid removal of the module



Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

Uninterruptible fieldbus operation when pulling the connector
Transmission rate up to 12 MBit/s
Easy assembly by screw connection
Shielding connection by strain relief

Application range

Plant engineering
Light & sound technology
Control engineering

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial connector)

Classification ETIM 6:

ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial connector)

Rated voltage (V):

30 V

Last Update (26.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® MC Module: PROFIBUS DP

Rated current (A):	1 A
Pollution degree:	3
Contacts:	Copper alloy, gold-plated
Number of contacts:	2 / 4 + shield
Termination methods:	Screw termination: for Profibus cable
Cycle of mechanical operation:	100
Temperature range:	-20 °C ... +85 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® MC Module: PROFIBUS DP

Article number	Article description	Contact type	Number of operating contacts	Slots	Pieces / PU
Module: Profibus DP					
10390400	MCS 2 SS	male	2 + shield	1	5
10390500	MCS 2 BS	female	2 + shield	1	5

Last Update (26.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16