

EPIC® MH 8.0mm Contacts

High flexibility by the use of any combination of inserts in one connector

Info

Modular connector system, plugable with the market standard





Supplementary automation components from Lapp



Mechanical and plant engineering



Rail



Wind Energy



Flame-retardant



Voltage

Crimp connection for permanent vibration proof contacting EPIC® MH system is mateable with the market standard

Application range

Mechanical engineering Robot-building Plant engineering Renewable energy Railway applications / vehicle construction

Technical Data

Classification ETIM 5:

Last Update (25.04.2024) ©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet.

ETIM 5.0 Class-ID: EC000796

PN 0456 / 02_03.16





EPIC® MH 8.0mm Contacts

ETIM 5.0 Class-Description: Contact for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000796

ETIM 6.0 Class-Description: Contact for industrial connectors

Contact resistance: < 5 mOhm

Termination methods: Crimp termination: 0.75 mm² ... 4.0 mm²

Stripping length (mm): 18

Cycle of mechanical operation: 500

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® MH 8.0mm Contacts

Article number	Article description	Contact type	Connection cross section (mm²)	Pieces / PU
EPIC® MH D=8.0 contacts				
44423242	EPIC® MH SCEM AG 10sqmm D=8.0	male	10	10
44423246	EPIC® MH BCEM AG 10sqmm D=8.0	female	10	10
44423243	EPIC® MH SCEM AG 16sqmm D=8.0	male	16	10
44423247	EPIC® MH BCEM AG 16sqmm D=8.0	female	16	10
44423244	EPIC® MH SCEM AG 25sqmm D=8.0	male	25	10
44423248	EPIC® MH BCEM AG 25sqmm D=8.0	female	25	10
44423245	EPIC® MH SCEM AG 35sqmm D=8.0	male	35	10
44423249	EPIC® MH BCEM AG 35sqmm D=8.0	female	35	10