

WM BW Blank cable marker

WM BW Blanc wrapping labels are markers of vinyl with an protective transparent foil for marking cables with a pen.

Info

Marking pens available in the web catalogue



Good chemical resistance



Halogen-free

Benefits

Wrapping label with protective foil

When the cover is applied onto the cable, the transparent foil covers the writing area, thus protecting it against abrasion, humidity, oil and light solvents.

Easy to label

Application range

For cable marking

The designations can be written with a pencil, a ballpoint, pen, or other marker on the white writing area

Indoor applications

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001288

ETIM 5.0 Class-Description: Labelling material

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001288

ETIM 6.0 Class-Description: Labelling material

Material:

Vinyl strips, silicone-treated lining, halogen-free

Temperature range:

-35°C to +70°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

FLEXIMARK® products are sold in packaging units. As example if you like to order 640 labels of LCK 32 you just need to order 1 PU instead of 640 single labels.

Last Update (12.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

WM BW Blank cable marker

Article number	Article designation	Labelling surface (mm)	For cable Ø (mm)	Number of markers per brochure	PU
61726150	WM brochure BW 3	25.0 x 25.0	8.0 - 40.0	30	1
61726160	WM brochure BW 5	20.0 x 25.0	6.0 - 18.1	60	1
61726170	WM brochure BW 12	15.0 x 12.0	5.0 - 5.4	200	1
61726180	WM brochure BW 14	15.0 x 6.0	5.0 - 5.4	400	1
61726190	WM brochure BW 34	14.0 x 18.0	5.0 - 10.0	140	1

Last Update (12.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16