ÖLFLEX® SERVO 719

Low capacitance servo cable with PVC outer sheath for static use - certified for North America

ÖLFLEX® SERVO 719 - low capacitance servo cable for fixed installation or occasional flexing with UL/cUL AWM certification

Info

Successor of ÖLFLEX® SERVO 700
Low-capacitance design
Without overall screening





Oil-resistant

UV-resistant

Benefits

One common cable for multiple circuits
Longer cable installation lengths thanks to low mutual capacitance cable design
Multi-standard certification reduces part varieties and saves costs
Space and weight-saving installations due to small cable diameters

Application range

Connecting cable between servo controller and motor
For static and occasionally flexible use
Plant engineering
Industrial machinery and machine tools
Printing machines

Product features

Low capacitance
Flammability:
UL/CSA: VW-1, FT1
IEC/EN: 60332-1-2

Last Update (23.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

ÖLFLEX® SERVO 719

Oil-resistant

Norm references / Approvals

USA: UL AWM Style 2570
Canada: cUL AWM Style I/II A/B FT1
UL File No. E63634

Product Make-up

Fine-wire, bare copper conductor
Core insulation: polypropylene (PP)
Individual design depending on the item: power cores without or with one or two individually screened control core pairs twisted together in short lay lengths
PVC outer sheath, black (RAL 9005)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	Power cores: black with marking U/L1/C/L+; V/L2; W/L3/D /L-; GN/YE protective conductor Single-paired versions: black; white Double-paired versions: black with white numbers 5; 6; 7; 8 0,34mm² pairs: WH/BN/GN/YE
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 6 x outer diameter
Nominal voltage:	Power cores and control cores: IEC U0/U: 600/1000 V UL & CSA: 1000 V
Test voltage:	Core/Core: 4 kV Core/Screen: 4 kV
Protective conductor:	G = with GN-YE protective conductor
Temperature range:	Occasional flexing: -5 °C to +70 °C (UL: +80 °C) Fixed installation: -40 °C to +80 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (23.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

LAPP

ÖLFLEX® SERVO 719

PRODUCT INFORMATION

Article number	Number of cores and mm² per conductor	Outer diameter (mm) approx.	Copper index (kg/km)	Weight (kg/km)
1020060	4 G 1,5 + (2 x 0,75)	9.7	83.3	177
1020065	4 G 1,5 + (2 x 1,5)	10.8	108.3	214
1020061	5 G 1,5 + (2 x 0,75)	10.6	97.7	203
1020062	7 G 1,5 + (2 x 0,75)	11.5	126.5	241
1020063	4 G 2,5 + (2 x 0,75)	11.1	121.7	238
1020066	4 G 2,5 + (2 x 1,5)	12.2	146.7	276
1020064	7 G 2,5 + (2 x 0,75)	12.7	193.7	325
1020067	4 G 4 + (2 x 1,5)	13.9	204.3	360
1020068	4 G 6 + (2 x 1,5)	16.1	281.1	478
1020069	4 G 10 + (2 x 1,5)	18.2	434.7	654
1020071	4 G 0,75 + 2 x (2 x 0,34)	9.0	62.1	121
1020072	4 G 1,5 + 2 x (2 x 0,75)	11.6	111.6	203
1020073	4 G 2,5 + 2 x (2 x 1,0)	13.6	159.7	286
1020074	4 G 4 + 2 x (2 x 1,0)	15.3	217.3	377
1020075	4 G 4 + (2 x 1,0) + (2 x 1,5)	15.5	237.6	396
1020076	4 G 6 + (2 x 1,0) + (2 x 1,5)	17.4	314.4	512

Last Update (23.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16