

## Copper rope Class 5

Fine-wired tinned copper rope for equipotential bonding systems

Copper rope - fine-wired tinned copper conductor for the construction of meshed equipotential bonding systems

### Info

For equipotential bonding systems



Halogen-free

### Benefits

Low impedance through tinning  
No corrosion of the tin coating

### Application range

For earthing devices and potential equalisation on machine parts and EDP systems  
For the Construction of meshed equipotential bonding systems

### Product Make-up

Fine-wire strand made of tinned-copper wires

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000993

ETIM 5.0 Class-Description: Single core cable

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000993

ETIM 6.0 Class-Description: Single core cable

Conductor stranding:

Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5

### Note

Last Update (03.11.2025)

©2025 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## Copper rope Class 5

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Packaging size: Coil  $\leq$  30 kg, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

\* Trade product, no Lapp product

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



## Copper rope Class 5

Article number	Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
4571212	6.0	3.1	57.6	48
4571213	10.0	4.1	96	86
4571214	16.0	5.3	153.6	130
4571215	25.0	6.4	240	203
4571216	35.0	7.5	336	290
4571217	50.0	9.0	480	407
4571218	70.0	10.7	672	600
4571219	95.0	12.3	912	795
4571220	120.0	14.1	1152	1000
4571221	150.0	16.0	1440	1220
4571222	185.0	18.0	1776	1500

Last Update (03.11.2025)

©2025 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03\_16