Extension- and compensating cables, multi-paired

PVC insulated - with and without steel wire armouring or foil screen

Extension and compensating cables, multi-paired version - suitable for use in temperature measurement and manufacturing process control

Info

Version SY - Armoured against
mechanical loads
Version ST - Screened against electro-
magnetical interference



Product Make-up

Version Y:
- Fine-wire conductor alloy
- PVC core insulation
- Cores twisted into layers
- PVC outer sheath

Version SY:
- Design as version Y
- Additional galvanised steel wire braiding
- PVC outer sheath

Version ST:
- Design as verison Y
- Cores twisted in pairs,
pairs twisted in layers
- Aluminium foil screening + drain wire
- PVC outer sheath

Design, for example PVC-PVC-S-PVC:
- PVC core insulation
- PVC inner sheath
- Steel wire braiding
- PVC outer sheath

Design, for example PVC-ST-PVC:
- PVC core insulation
- STatic foil screen
- PVC outer sheath

Colour identity code
DIN 43710
Negative conductor and outer sheath:
Fe/CuNi: blue
NiCr/Ni: green

Last Update (22.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

Extension- and compensating cables, multi-paired

PtRh/Pt: white
Positive conductor: always red
IEC 60 584
Positive conductor and outer sheath:
Fe/CuNi: black
NiCr/Ni: green
PtRh/Pt: orange
Negative conductor: always white
Extension-conductor alloys are identified with X, e.g. JX (Fe/CuNi)
Compensating-conductor alloys are identified with C, e.g. KCA (NiCr/Ni)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000838 ETIM 5.0 Class-Description: Thermocouple cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000838 ETIM 6.0 Class-Description: Thermocouple cable
Core identification code:	From 4 cores in pairs with consecutively marked numbers (1-1, 2-2, 3-3, 4-4...)
Based on:	Limiting deviation in accordance with DIN and IEC in accordance with class 2
Conductor stranding:	48 x 0.20 mm
Minimum bending radius:	For flexible use: 12.5 x outer diameter Type SY with steel braid: 15 x outer diameter Type ST with foil screen: 15 x outer diameter
Temperature range:	(referring to insulation and sheath material) Flexing: -5 °C to +80 °C Fixed installation: -40 °C to +80 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2023 Lapp Group - Technical changes reserved

Extension- and compensating cables, multi-paired

Article number	Thermocouple	Product Make-up	Cable design	Number of cores and mm² per conductor	Outer diameter [mm]	Weight (kg/km)
Type Y without steel wire braiding						
0155001	Fe/CuNi	DIN-LX	PVC-PVC	4 x 1.5	8.2	130
0165001	Fe/CuNi	IEC-JX	PVC-PVC	4 x 1.5	8.2	130
0156001	NiCr/Ni	DIN-KCA	PVC-PVC	4 x 1.5	8.2	130
0166001	NiCr/Ni	IEC-KCA	PVC-PVC	4 x 1.5	8.2	130
0157001	PtRh/Pt	DIN-RCB/SCB	PVC-PVC	4 x 1.5	8.2	130
0167001	PtRh/Pt	IEC-RCB/SCB	PVC-PVC	4 x 1.5	8.2	130
0155002	Fe/CuNi	DIN-LX	PVC-PVC	6 x 1.5	10.2	200
0165002	Fe/CuNi	IEC-JX	PVC-PVC	6 x 1.5	10.2	200
0156002	NiCr/Ni	DIN-KCA	PVC-PVC	6 x 1.5	10.2	200
0166002	NiCr/Ni	IEC-KCA	PVC-PVC	6 x 1.5	10.2	200
0157002	PtRh/Pt	DIN-RCB/SCB	PVC-PVC	6 x 1.5	10.2	200
0167002	PtRh/Pt	IEC-RCB/SCB	PVC-PVC	6 x 1.5	10.2	200
0155003	Fe/CuNi	DIN-LX	PVC-PVC	8 x 1.5	11.2	238
0165003	Fe/CuNi	IEC-JX	PVC-PVC	8 x 1.5	11.2	238
0156003	NiCr/Ni	DIN-KCA	PVC-PVC	8 x 1.5	11.2	238
0166003	NiCr/Ni	IEC-KCA	PVC-PVC	8 x 1.5	11.2	238
0155005	Fe/CuNi	DIN-LX	PVC-PVC	12 x 1.5	13.3	335
0165005	Fe/CuNi	IEC-JX	PVC-PVC	12 x 1.5	13.3	335
0155007	Fe/CuNi	DIN-LX	PVC-PVC	16 x 1.5	15	447
0165007	Fe/CuNi	IEC-JX	PVC-PVC	16 x 1.5	15	447
0156007	NiCr/Ni	DIN-KCA	PVC-PVC	16 x 1.5	15	447
0166007	NiCr/Ni	IEC-KCA	PVC-PVC	16 x 1.5	15	447
0155010	Fe/CuNi	DIN-LX	PVC-PVC	24 x 1.5	19	555
0165010	Fe/CuNi	IEC-JX	PVC-PVC	24 x 1.5	19	555
0156010	NiCr/Ni	DIN-KCA	PVC-PVC	24 x 1.5	19	555
0166010	NiCr/Ni	IEC-KCA	PVC-PVC	24 x 1.5	19	555
Type SY with steel wire braiding						
0155501	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0165501	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0156501	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0166501	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0157501	PtRh/Pt	DIN-RCB/SCB	PVC-PVC-S-PVC	4 x 1.5	11.4	240
0167501	PtRh/Pt	IEC-RCB/SCB	PVC-PVC-S-PVC	4 x 1.5	11.4	240

Last Update (22.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

Extension- and compensating cables, multi-paired

Article number	Thermocouple	Product Make-up	Cable design	Number of cores and mm² per conductor	Outer diameter [mm]	Weight (kg/km)
0155502	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	6 x 1.5	13	355
0165502	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	6 x 1.5	13	355
0156502	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	6 x 1.5	13	355
0166502	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	6 x 1.5	13	355
0157502	PtRh/Pt	DIN-RCB/SCB	PVC-PVC-S-PVC	6 x 1.5	13	355
0167502	PtRh/Pt	IEC-RCB/SCB	PVC-PVC-S-PVC	6 x 1.5	13	355
0155503	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0165503	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0156503	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0166503	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	8 x 1.5	13.8	410
0155505	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0165505	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0156505	NiCr/Ni	DIN-KCA	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0166505	NiCr/Ni	IEC-KCA	PVC-PVC-S-PVC	12 x 1.5	17.9	550
0155507	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	16 x 1.5	19.4	730
0165507	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	16 x 1.5	19.4	730
0155510	Fe/CuNi	DIN-LX	PVC-PVC-S-PVC	24 x 1.5	23.8	847
0165510	Fe/CuNi	IEC-JX	PVC-PVC-S-PVC	24 x 1.5	23.8	847
Type ST with static overall screening						
0158500	Fe/CuNi	DIN-LX	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0168500	Fe/CuNi	IEC-JX	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0158501	NiCr/Ni	DIN-KCA	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0168501	NiCr/Ni	IEC-KCA	PVC-ST-PVC	2 x 2 x 1.5	11.4	145
0158503	Fe/CuNi	DIN-LX	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0168503	Fe/CuNi	IEC-JX	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0158504	NiCr/Ni	DIN-KCA	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0168504	NiCr/Ni	IEC-KCA	PVC-ST-PVC	4 x 2 x 1.5	13.7	257
0158506	Fe/CuNi	DIN-LX	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0168506	Fe/CuNi	IEC-JX	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0158507	NiCr/Ni	DIN-KCA	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0168507	NiCr/Ni	IEC-KCA	PVC-ST-PVC	8 x 2 x 1.5	18.3	469
0158509	Fe/CuNi	DIN-LX	PVC-ST-PVC	12 x 2 x 1.5	22.2	573
0168509	Fe/CuNi	IEC-JX	PVC-ST-PVC	12 x 2 x 1.5	22.2	573
0158510	NiCr/Ni	DIN-KCA	PVC-ST-PVC	12 x 2 x 1.5	22.2	573

Last Update (22.12.2023)
©2023 Lapp Group - Technical changes reserved

Extension- and compensating cables, multi-paired

Article number	Thermocouple	Product Make-up	Cable design	Number of cores and mm² per conductor	Outer diameter [mm]	Weight (kg/km)
0168510	NiCr/Ni	IEC-KCA	PVC-ST-PVC	12 x 2 x 1.5	22.2	573

©2023 Lapp Group - Technical changes reserved