

SILVYN® HFX

SILVYN® HFX is a liquidtight, chemical resistant conduit with interlocked profile and a PUR jacket



Suitable for outdoor use



Good chemical resistance



Halogen-free



Cold-resistant



Mechanical resistance



Oil-resistant



Robust



Reliability



Temperature-resistant



UV-resistant



Waterproof

SILVYN® HFX



Benefits

Impact-resistant
Robust
Abrasion protection
High resistance to oil, petrol, acids and greases
Liquidtight

Application range

Mechanical engineering
Paper industry
Measurement and control technology
Railway applications
Outdoors

Product features

UV-resistant
Halogen-free and flame-retardant
High mechanical and chemical resistance

Product Make-up

Spirally-wound heavy metal protective conduit with roughened profile
PUR outer sheath

Note

PU = 10m (on request)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001179 ETIM 5.0 Class-Description: Protective metallic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001179 ETIM 6.0 Class-Description: Protective metallic hose
On request:	Longer lengths on drums 10m coils are available upon request
Colour delivered:	Black
Material:	Metal with PUR sheath
Temperature range:	-55 °C to +105 °C Short-term up to +125 °C

Note

* Trade product, no Lapp product

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



SILVYN® HFX

Article number	Nominal size	ID x OD mm	Bending radius (mm)	PU ring (m)
SILVYN® HFX				
64400200	5/16"	10.1 x 14.4	65	30
64400210	3/8"	12.6 x 17.8	85	30
64400220	1/2"	16 x 21.1	110	30
64400230	3/4"	21 x 26.4	140	30
64400240	1"	26.5 x 33.1	170	30
64400250	1 1/4"	35.1 x 41.8	215	15
64400251	1 1/2"	40.3 x 47.8	250	15
64400252	2"	51.6 x 59.9	300	15