

## SILVYN® FPAX NPT

SILVYN® FPAX NPT - IP68/IP69 conduit fitting for SILVYN® FPAS

### Info

IP66

IP67

IP68 (2bar)

IP69



Maximum vibration protection



Assembly time



Optimum strain relief



Temperature-resistant



UV-resistant



Waterproof



Variety of approval certifications

### Benefits

Fast assembly

High tensile strength

Watertight

Vibration protection

Last Update (05.09.2020)

©2020 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## SILVYN® FPAX NPT

### Application range

In combination with protective conduit:  
SILVYN® FPAS  
Applications with strong vibrations

### Product features

In black colour UV-resistant and weather-proofed  
Removeable with a screwdriver

### Norm references / Approvals

UL FILENUMBER E308201

### Product Make-up

NPT connection thread  
Body with inner sealing  
Upper part with integrated all-round tothing

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001176 ETIM 5.0 Class-Description: Screw connection for corrugated plastic hose
Certifications:	IEC EN 61386-23
Colour delivered:	Black (RAL 9005), UV-resistant
Material:	PA66 Halogen-free
Protection rating:	IP66 IP67 IP68 (2bar) IP69
Temperature range:	-50°C to +135°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SILVYN® FPAX NPT**

Article number	Nominal size	Suitable for SILVYN® FPAS	Pieces / PU
SILVYN® FPAX NPT black			
55507700	NPT 3/8"	16	10
55507710	NPT 1/2"	16	10
55507720	NPT 1/2"	21	10
55507730	NPT 3/4"	28	10
55507740	NPT 1"	34	10
55507750	NPT 1 1/4"	42	2
55507760	NPT 1 1/2"	42	2
55507770	NPT 1 1/2"	54	2
55507780	NPT 2"	54	2
55507790	NPT 2"	67	2

Last Update (05.09.2020)

©2020 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16