


## SILVYN® SHRINK BRAID PET

SILVYN® SHRINK BRAID PA6 - shrinkable braided sleeving

### Info

Shrinkable abrasion protection



Wide clamping range



Low weight



Reliability



Temperature-resistant



UV-resistant

### Benefits

Additional abrasion protection for critical areas  
Cut into length without frizzle on the conduit's end  
Simple, fast cable bundling  
Protection against dust

### Application range

Easy cable protection  
Additional insulation  
Bundling and guiding of cables and wires  
Low rodent-protection

### Product features

Abrasion-resistant  
Flexible  
Shrinkable  
Shrinking ratio: 2:1  
Maximum length lost after shrinkage is less than 15 %

Last Update (14.02.2025)

©2025 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## SILVYN® SHRINK BRAID PET

### Product Make-up

Polyester - PET with shrinkable Polyolefin fibres

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001182 ETIM 5.0 Class-Description: Braided hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001182 ETIM 6.0 Class-Description: Braided hose
On request:	Bulk containers on rolls More sizes available
Note:	No dielectric strength Self extinguishing acc. to UL94 HB
Colour delivered:	Black (RAL 9005), UV-resistant
Material:	Polyester - PET with shrinkable Polyolefin fibres
Temperature range:	-40 °C to +150 °C Processing: min. +180 °C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



## SILVYN® SHRINK BRAID PET

Article number	Nominal size	Shrinkage range mm	Colour	PU (m)
SILVYN® SHRINK BRAID PET				
61721270	12/06	12 - 6	black	5
61721271	25/12	25 - 12	black	5
61721272	30/15	30 - 15	black	5
61721273	50/25	50 - 25	black	4
61721274	70/35	70 - 35	black	4

Last Update (14.02.2025)

©2025 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03\_16