

SILVYN® FPS-EDU

SILVYN® FPS-EDU is a highly flexible protection conduit made of PVC with steel wire braiding

Info

High flexible and mechanical protection at the same time



Mechanical resistance



Power chain



Reliability



Torsion-resistant



Waterproof

Benefits

Protects against hot chips
High-tensile
Highly flexible
Air-tight and impermeable
mechanical resistance

Application range

Mechanical engineering
Plant engineering
Automation technology
Used in areas where cables and wires could be damaged by welding sparks and hot chips
Robotics industry

Product Make-up

PVC-insulated steel spring wire
Soft PVC outer sheath
Galvanised steel wire braiding

Last Update (19.03.2026)

©2026 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® FPS-EDU**Note**

PU = 10m (on request)

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001177

ETIM 5.0 Class-Description: Protective plastic hose

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001177

ETIM 6.0 Class-Description: Protective plastic hose

Material:

insulated spring steel wire with Soft PVC and galvanized steel braid

Temperature range:

-25°C to +90°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



SILVYN® FPS-EDU

Article number	Nominal size	ID x OD mm	Bending radius (mm)	Suitable for SILVYN® MSK-M	Suitable for SILVYN® US-M	Suitable for SILVYN® US	PU ring (m)
SILVYN® FPS-EDU							
61802330	14	9.0 x 14.0	16	16 x 1,5	16 x 1,5	9	50
61802331	17	12.0 x 17.0	19	20 x 1,5	20 x 1,5	11	50
61802333	21	15.0 x 21.0	24	25 x 1,5	20 x 1,5	16	50
61802334	27	20.0 x 27.0	30	32 x 1,5	25 x 1,5	21	50
61802335	36	28.0 x 36.0	40	40 x 1,5	32 x 1,5	29	25
61802336	45	37.0 x 45.0	48	50 x 1,5	40 x 1,5	36	25
61802337	56	48.0 x 56.0	60	63 x 1,5	50 x 1,5	48	25

Last Update (19.03.2026)

©2026 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16