SILVYN® US-M EE

SILVYN® US-M is a nickel-plated brass conduit fitting that offers IP40 / IP54 / IP66 protection degree depending on the used conduit





Maximum vibration protection

Space requirement

Robust

Temperature-resistant

Benefits

High tensile strength
Space-saving
Vibration protection
All-purpose
Fast and easy assembly

Application range

In combination with protective conduit:
SILVYN® FPS
SILVYN® FD-PU
Mechanical engineering
Plant engineering

Product features

Compact design

Product Make-up

Last Update (23.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SILVYN® US-M EE

Metric connection thread
Hexagonal collar
Threaded sleeve
Sealing element
Cap nut

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001180 ETIM 5.0 Class-Description: Screw connection for protective metallic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001180 ETIM 6.0 Class-Description: Screw connection for protective metallic hose
Material:	Body: nickel-plated brass Sealing ring: TPE
Protection rating:	IP 54 (with SILVYN® FPS, FD-PU)
Temperature range:	-40 °C to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2023 Lapp Group - Technical changes reserved

LAPP

SILVYN® US-M EE

PRODUCT INFORMATION

Article number	Metric size	Clear opening (mm)	Suitable for SILVYN® FPS/FD-PU	Pieces / PU
SILVYN® US-M for SILVYN® FPS / FD-PU				
55502601	10 x 1.0	6	10	50
55502602	12 x 1.5	9	14	50
55502603	16 x 1.5	11.5	17	50
55502604	20 x 1.5	14.5	21	50
55502605	25 x 1.5	19.5	27	25
55502606	32 x 1.5	26.5	36	25
55502607	40 x 1.5	35	45	20
55502608	50 x 1.5	45.5	56	10
55502609	63 x 1.5	45.5	56	10

Last Update (23.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SILVYN® US-M EE



Last Update (23.12.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16