

Ty-Rap® Heat-resistant cable ties with steel nose

The TY- RAP® with steel nose is also available as heat-resistant cable tie which withstands temperatures up to 105°C.



Halogen-free

Benefits

Contains all the advantages of TY-RAP®, with higher heat-resistance

Application range

Can be used in areas exposed to high temperatures such as electrical heating devices or heating installations

Norm references / Approvals

File number: E49405, see table

Fire behaviour according to UL94 V-2

Design

Heat-resistant cable ties have the extension "M"

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000046 ETIM 5.0 Class-Description: Cable tie
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000046 ETIM 6.0 Class-Description: Cable tie
Colour delivered:	Light green- transparent
Material:	Heat-resistant polyamide 6.6 Halogen-free and silicone-free
Temperature range:	-40 °C to +105 °C

Note

TY-RAP® is a registered trademark of ABB.

Last Update (14.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

Ty-Rap® Heat-resistant cable ties with steel nose

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Ty-Rap® Heat-resistant cable ties with steel nose

Article number	Article description	UL certification	Length x width (mm)	Bundling Ø (mm)	Tensile strength (N)	Pieces / PU
61723470	TYH 23 M	yes	92.0 x 2.4	2 - 16	80	1000
61723460	TYH 232 M	yes	203.0 x 2.4	2 - 50	80	1000
61723440	TYH 24 M	yes	140.0 x 3.6	2 - 29	130	1000
61723430	TYH 242 M	no	208.0 x 3.6	2 - 50	130	1000
61723410	TYH 26 M	yes	284.0 x 3.6	2 - 76	130	1000
61723420	TYH 25 M	yes	186.0 x 4.8	3.5 - 45	220	1000
61723380	TYH 28 M	yes	360.0 x 4.8	3.5 - 102	220	1000
61723390	TYH 272 M	yes	222.0 x 7.6	6 - 50	540	500
61723400	TYH 27 M	yes	340.0 x 7.0	6 - 90	540	500
61723350	TYH 29 M	yes	771.0 x 6.9	6 - 229	530	500

Last Update (14.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16