DSA 0110 + DSA 0725 crimping pliers

DSA 0110 and DAS 0725: Crimping pliers for pressing insulated connectors as insulated cable lugs and blade/panel connectors from 0,1 to 1,5 mm2 and 0,5-2,5 mm2





Reliability

Benefits

Suitable for left and right-handed users
Less force required for perfect pressing
Clearly marked press moulds
Cross-section of press matrix is embossed in the cable lugs for checking
Pressing according to the forced finish system

Application range

Safety pressing pliers for insulated connections
For insulated cable lugs, blade connectors and other connectors

Product features

Emergency release, if the pressing operation needs to be interrupted

Norm references / Approvals

Tested in accordance with DIN standards

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000168 ETIM 5.0 Class-Description: Crimp tool cable lugs, cable end sleeves, screen connection
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000168 ETIM 6.0 Class-Description: Crimp tool cable lugs, cable end sleeves, screen connection
General:	Adjustable crimping pressure
Note:	Crimping profile: Oval

Note

Last Update (22.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

DSA 0110 + DSA 0725 crimping pliers

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (22.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

DSA 0110 + DSA 0725 crimping pliers

Article number	Article designation	For mm²	Weight (kg)	Length (mm)	Pieces / PU
61722050	DSA 0110	0.1 - 1.5	0.35	225	1
61722060	DSA 0725	0.5 - 2.5	0.35	192	1

Last Update (22.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16