

Tube cable lugs V2A

Tube cable lug made of V2A stainless steel, heat-resistant up to +400°C, for use with ÖLFLEX® HEAT cables/single cores, available in different dimensions.



Food & Beverage



Mechanical and plant engineering



Oil & Gas



Rail



Suitable for outdoor use



Good chemical resistance



Halogen-free



Heat-resistant



Maximum vibration protection



Mechanical resistance



Oil-resistant



Acid-resistant

Last Update (02.05.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

Tube cable lugs V2A



Temperature-resistant

Benefits

Withstand temperatures up to +400 °C.

Compatible with equally heat-resistant ÖLFLEX® HEAT cables/single cores.

Suitable for use with KLAUKE crimping tools.

The flat mounting surface and precise processing simplify the crimping process.

Application range

For creating a safe crimp connection with multi-wire and fine-wire round cables in classes 2 and 5 in accordance with DIN EN 60228.

Resistant to corrosion and acid.

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001051

ETIM 5.0 Class-Description: Tube cable lug for copper conductors

Material:

stainless steel V2A

Temperature range:

Temperature (max.) +400 °C

Note

* Trade product, no Lapp product

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Tube cable lugs V2A

| Article number | UL certification | Length (mm) | d mm |
|----------------|------------------|-------------|------|
| 63207037 | no | 17.5 | 1.6 |
| 63207038 | no | 19 | 1.6 |
| 63207039 | no | 22 | 3 |
| 63207041 | no | 22 | 3 |
| 63207042 | no | 25.5 | 3 |
| 63207043 | no | 23 | 4 |
| 63207044 | no | 25 | 4 |
| 63207045 | no | 26 | 4 |
| 63207046 | no | 28.5 | 5 |
| 63207047 | no | 28.5 | 5 |
| 63207048 | no | 34 | 6 |
| 63207049 | no | 33.5 | 6 |
| 63207051 | no | 34 | 6 |
| 63207052 | no | 37.5 | 6 |

Last Update (02.05.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16