

# PRODUCT INFORMATION

# E-PEW 12 universal tool

E-PEW 12: electromechanical tool with Li-ion battery is compatible with crimp dies for the PEW 12 system



## **Benefits**

Electromechanical tool with Li-lon battery Dependable, reliable, low maintenance Precise tap positioning of contacts Quickstop, no overcrimping Process monitoring on multifunction display:

- Battery charge level

- Service interval display

- Overheating / overload warning

### Application range

Compatible with the crimping dies for the PEW 12 system (crimping dies either fit into PEW 12 or PEW 12S) Crimping of almost all crimped connections with conductor cross-sections 0.08-95 mm<sup>2</sup> Various applications in the cable assembly

### Included

Supplied in plastic case (500 x 420 x 125 mm) Tool without crimping dies and locators Including battery and battery recharger

## **Technical Data**

 Classification ETIM 5:
 ETIM 5.0 Class-ID: EC000168

 ETIM 5.0 Class-Description: Crimp tool cable lugs, cable end sleeves, screen connection

 Classification ETIM 6:
 ETIM 6.0 Class-ID: EC000168

 ETIM 6.0 Class-ID: EC000168

 ETIM 6.0 Class-Description: Crimp tool cable lugs, cable end sleeves, screen connection

 Classification ETIM 6:
 ETIM 6.0 Class-ID: EC000168

 ETIM 6.0 Class-Description: Crimp tool cable lugs, cable end sleeves, screen connection

 Colour delivered:
 Black

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (19.12.2024) ©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02\_03.16

rticle number	Article designation	Weight (kg)
1813817	E-PEW 12	4.7
-		

# E-PEW 12 universal tool

©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02\_03.16